

MPT210

Body Worn Camera

- · 2.8 inch touch screen, 8-core 2GHz CPU
- Support 30fps@2K(2560*1440) recording, the image resolution up to 34MP(7808*4400)
- · H.265/H.264 high compression coding
- Horizontal field 120°, image distortion is less than 20%
- Support one-key to start video/audio recording
- Support laser positioning LED light, IR mode, OSD overlay, pre-record and post-record
- Support 4G, WIFI, NFC, bluetooth, GPS, GLONASS, Beidou and compass
- Battery capacity is 3200MAh (4.35V), support change battery without power loss in 15 minutes
- · Support IP67, drop proof 2 meters









System Overview

MPT210 is a body worn camera which can be used as a law-enforcement video recoder. This device support one key to starthigh-definition real-time recording and all the information such as GPS and video can be uploaded to VMS by wireless network: 3G/4G/WIFI.It can also support audio communication between devices in one group. The supported wireless network band are below:

CDMA EVDO:BC0 GSM: B2/B3/B5/B8 WCDMA: B1/B2/B5/B8 TD-SCDMA: B34/B39 LTE-FDD:B1/B3/B5

LTE-TDD: B38/B39/B40/B41

This individual portable audio&video recorder designed for particular fields or departments, such as police, military, urban management, forensic,insurance, energy resources and etc.

Functions

One key recording and remote live monitor
Press one button to trigger to start audio or video recording, and
with wireless network, the video can be sent to VMS, and on
VMS client, it can do remote live monitor.

Group talking

Administrator can build groups and add different users into one group, users can talk and send message to other members in this group.

3G/4G/WIFI

Embedded with 3G/4G/WIFI module, the device can register into a public network to connect with VMS, and can send all the information(video/audio/alarm/gps) through wireless network.

GPS

Embedded GPS module can receive location information and upload to VMS, and the user can be tracked on the electric map of VMS.

Alarm push

When in emergency, users can press the alarm button to trigger an alarm and send to VMS.

Body Worn Camera | MPT210

Dimensions (mm)

| Technical Specification | | Screen | |
|-------------------------|--|---------------------|---|
| System | | Dimension | 2.8 inch colour LCD |
| Main Processor | 2G 8-core CPU | Auxiliary interface | |
| Operating System | Android 6.0.1 | USB | 1 micro USB, support OTG |
| Video | | SIM card slot | 1 micro SIM card slot |
| Record Resolution | 2K(2560*1440) /1080P/720P/WVGA | Network | |
| Compression | H.265/H.264 | Positioning system | GPS/GLONASS/BEIDOU/AG |
| Image Resolution | 34 MP (7808x4392) | Cellular | Support 4G(FDD-LTE) |
| Wide-angle | 120° | WiFi | Support 802.11b/g/n/ac, su |
| IR | Max. IR Length 10m, support auto/manual mode to switch | NFC | Support |
| Digital zoom | 8x | Bluetooth | Support Bluetooth 4.1 |
| Pre-record | ≤60s | Battery | |
| Post-record | ≤60s | Capacity | 4.35V/3200mAh.Removable battery without switching o |
| Laser positioning | Support | Standby Time | 7 days |
| Key event mark | Support to mark the important video | Recording Time | 13h 30fps@1080p recording |
| | | Battery change | Support |
| OSD overlay | Support to overlay the recording time/ID/GPS etc | General | |
| Storage | | Ingress Protection | IP67 |
| RAM | 2G | | |
| ROM | 32G | Drop proof | 2 meters |
| | | Working temperature | -30℃~55℃ |

| Screen | | |
|---------------------|---|--|
| Dimension | 2.8 inch colour LCD | |
| Auxiliary interface | | |
| USB | 1 micro USB, support OTG | |
| SIM card slot | 1 micro SIM card slot | |
| Network | | |
| Positioning system | GPS/GLONASS/BEIDOU/AGPS | |
| Cellular | Support 4G(FDD-LTE) | |
| WiFi | Support 802.11b/g/n/ac, support 2.4G/5G | |
| NFC | Support | |
| Bluetooth | Support Bluetooth 4.1 | |
| Battery | | |
| Capacity | 4.35V/3200mAh.Removable. Support replacing battery without switching off the device | |
| Standby Time | 7 days | |
| Recording Time | 13h 30fps@1080p recording | |
| Battery change | Support | |
| General | | |
| Ingress Protection | IP67 | |
| Drop proof | 2 meters | |
| Working temperature | -30℃~55℃ | |
| Dimension(mm) | 102x63.6x28.6mm | |
| Weight | 215g(with clamp) | |
| | | |