

# DH-PFM320D-EN/BS/US

12V 2A Power Adapter



## Features

- Easy installation
- With indicator light working
- Support  $-30^{\circ}\text{C} \sim +70^{\circ}\text{C}$  wide-range temperature operation, and the full load efficiency of the power supply can be up to 100% at these temperatures
- Accurate overcurrent, overvoltage protection

## Technical Specifications

Model	DH-PFM320D-EN	DH-PFM320D-BS	DH-PFM320D-US (VI)
<b>Electrical Specification</b>			
Input	100~240V, 50/60Hz, 0.6A		
Output	12V, 2A(+7% , -3%)		
<b>Protection/Environmental</b>			
Protection	<ul style="list-style-type: none"> <li>Surge protection, over temperature protection,</li> <li>over current, voltage load protection</li> </ul>		
	ESD: EN61000-4-2 +/-4kV Contact; +/-8kV Air		
	Surge: EN61000-4-5" Combination Wave: Common Mode ± 4KV (12 ohms); Differential Mode ± 2kV (2 ohms)		
Working temperature	<b>-30°C ~ +70°C (-22°F ~ +158°F)</b>		
Working humidity	<95% RH		
<b>Physical Properties</b>			
Weight	170g(0.37lb)		
Dimension(LxWxH)	104mmx45mmx33mm(4.09"x1.77"x1.3")		
Installation mode	Plane installation		
Color	Black		
Input plug	2-pin Euro plug	3-pin British plug	2-pin North American plug
Outgoing cord	AC wire: 50cm(19.69"), DC wire: 80cm(31.5")		
DC plug	Φ5.5mmxΦ2.1mmx12mm(Φ0.22"xΦ0.08"x0.47mm)		
<b>Safety Standards</b>			
Certification	CE, FCC, UL-VI		

## Order Information

Type	Part Number	Description
Power	DH-PFM321D-EN	DC12V 1A Power Adapter _ Dahua brand, European standard
	DH-PFM321D-BS	DC12V 1A Power Adapter _ Dahua brand, British standard
	DH-PFM321D-US	DC12V 1A Power Adapter(VI) _ Dahua brand, North American standard
	<b>DH-PFM320D-EN</b>	DC12V 2A Power Adapter _ Dahua brand, European standard
	<b>DH-PFM320D-BS</b>	DC12V 2A Power Adapter _ Dahua brand, British standard
	<b>DH-PFM320D-US</b>	DC12V 2A Power Adapter(VI) _ Dahua brand, North American standard

Dimensions (mm/inch)

